

*Element***COLOURS:****SILICON****PORTLAND****PAPYRUS****LIME****CEMENT****FINISHES:****SIZES:****GRIP**

603 X 603 X 10 MM

**NATURAL**

452 X 452 X 9MM, 600 X 300 X 10MM, 600 X 600 X 10 MM, 603 X 603 X 10 MM, 900 X 225 X 11MM, 900 X 450 X 11 MM, 900 X 900 X 11 MM

**GRIP**

603 X 603 X 10 MM

**NATURAL**

452 X 452 X 9MM, 600 X 300 X 10MM, 600 X 600 X 10 MM, 603 X 603 X 10 MM, 900 X 225 X 11MM, 900 X 450 X 11 MM, 900 X 900 X 11 MM

**GRIP**

603 X 603 X 10 MM

**NATURAL**

452 X 452 X 9MM, 600 X 300 X 10MM, 600 X 600 X 10 MM, 603 X 603 X 10 MM, 900 X 225 X 11MM, 900 X 450 X 11 MM, 900 X 900 X 11 MM

**GRIP**

603 X 603 X 10 MM

**NATURAL**

452 X 452 X 9MM, 600 X 300 X 10MM, 600 X 600 X 10 MM, 603 X 603 X 10 MM, 900 X 225 X 11MM, 900 X 450 X 11 MM, 900 X 900 X 11 MM

**GRIP**

603 X 603 X 10 MM

**NATURAL**

452 X 452 X 9MM, 600 X 300 X 10MM, 600 X 600 X 10 MM, 603 X 603 X 10 MM, 900 X 225 X 11MM, 900 X 450 X 11 MM, 900 X 900 X 11 MM

## SLIP RESISTANCE

Any queries about slip resistance please contact us.

## APPLICATION

Element is suitable for:

PTV

96 Rubber

55 Rubber

|  | Wet | Dry | Wet | Dry | R Rating |
|--|-----|-----|-----|-----|----------|
|--|-----|-----|-----|-----|----------|

|         |     |     |     |     |    |
|---------|-----|-----|-----|-----|----|
| Natural | AOR | AOR | AOR | AOR | R9 |
|---------|-----|-----|-----|-----|----|

|      |     |     |     |     |           |
|------|-----|-----|-----|-----|-----------|
| Grip | AOR | AOR | AOR | AOR | R11 A+B+C |
|------|-----|-----|-----|-----|-----------|

## ORDER A FREE SAMPLE

+44(0) 24 7642 2580

Request 100 X 100 sample

design@kinorigo.com

Colour representations on this sheet may not be exact.  
Take care when choosing your tiles, make sure you order a sample

## Technical Specifications

|                         | Norm            | Average value            |
|-------------------------|-----------------|--------------------------|
| Water absorbtion        | EN ISO 10545_3  | <0.05%                   |
| Abrasion resistance     | EN ISO 10545_6  | <145mm <sup>3</sup>      |
| Flexular strength (MOR) | EN ISO 10545_4  | >50 N/mm <sup>2</sup>    |
| Slip resistance         | DIN 51130       | R9 Nat<br>R11 A+B+C Grip |
| Frost resistance        | EN ISO 10545_12 | YES                      |
| Stain resistance        | EN ISO 10545_14 | YES                      |

## Packaging Information

| Finish       | Size             | Pieces/box | Weight/box | Sqm/box | Boxes/pallet | Weight/pallet | Sqm/pallet |
|--------------|------------------|------------|------------|---------|--------------|---------------|------------|
| Natural      | 900 x 900 x 11mm | 2          | 40,0       | 1,62    | 15           | 600,0         | 24,30      |
| Natural      | 900 x 450 x 11mm | 3          | 30,0       | 1,215   | 30           | 900,0         | 36,45      |
| Natural      | 900 x 225 x 11mm | 4          | 20,0       | 0,810   | 44           | 880,0         | 35,64      |
| Natural/Grip | 603 x 603 x 10mm | 4          | 32,5       | 1,454   | 32           | 1040,0        | 46,541     |
| Natural      | 600 x 600 x 10mm | 4          | 32,0       | 1,44    | 32           | 1024,0        | 46,08      |
| Natural      | 600 x 300 x 10mm | 8          | 32,0       | 1,44    | 32           | 1024,0        | 46,08      |
| Natural      | 452 x 452 x 9mm  | 8          | 33,90      | 1,634   | 52           | 1762,8        | 84,989     |



ELEMENT CEMENT



ELEMENT CEMENT



ELEMENT CEMENT





ELEMENT LIME



ELEMENT PAPYRUS



ELEMENT PAPYRUS



ELEMENT PAPYRUS





ELEMENT PAPYRUS



ELEMENT PAPYRUS



ELEMENT PAPYRUS



ELEMENT PAPYRUS





ELEMENT PAPYRUS



ELEMENT PAPYRUS





ELEMENT PAPYRUS



ELEMENT SILICON



