




COLOURS:**MILK****CLOUD****ASH****RICE****FINISHES:****SIZES:****HONED**

1200 X 200 X 10.5MM, 1200 X 600 X 10.5 MM, 600 X 600 X 10.5 MM, 800 X 800 X 10.5MM

NATURAL

1200 X 200 X 10.5MM, 1200 X 600 X 10.5 MM, 600 X 300 X 10.5 MM, 600 X 600 X 10.5 MM, 800 X 800 X 10.5MM

GRIP

1200 X 200 X 10.5MM, 1200 X 600 X 10.5 MM, 600 X 600 X 10.5 MM

NATURAL

1200 X 200 X 10.5MM, 1200 X 600 X 10.5 MM, 600 X 300 X 10.5 MM, 600 X 600 X 10.5 MM, 800 X 800 X 10.5MM

HONED

1200 X 200 X 10.5MM, 1200 X 600 X 10.5 MM, 600 X 600 X 10.5 MM, 800 X 800 X 10.5MM

GRIP

1200 X 200 X 10.5MM, 1200 X 600 X 10.5 MM, 600 X 600 X 10.5 MM

NATURAL

1200 X 200 X 10.5MM, 1200 X 600 X 10.5 MM, 600 X 300 X 10.5 MM, 600 X 600 X 10.5 MM, 800 X 800 X 10.5MM

HONED

1200 X 200 X 10.5MM, 1200 X 600 X 10.5 MM, 600 X 600 X 10.5 MM, 800 X 800 X 10.5MM

GRIP

1200 X 200 X 10.5MM, 1200 X 600 X 10.5 MM, 600 X 600 X 10.5 MM

NATURAL

1200 X 200 X 10.5MM, 1200 X 600 X 10.5 MM, 600 X 300 X 10.5 MM, 600 X 600 X 10.5 MM, 800 X 800 X 10.5MM

HONED

1200 X 200 X 10.5MM, 1200 X 600 X 10.5 MM, 600 X 600 X 10.5 MM, 800 X 800 X 10.5MM

GRIP

1200 X 200 X 10.5MM, 1200 X 600 X 10.5 MM, 600 X 600 X 10.5 MM

MM



ROPE

NATURAL

1200 X 200 X 10.5MM, 1200 X 600 X 10.5 MM, 600 X 300 X 10.5 MM, 600 X 600 X 10.5 MM, 800 X 800 X 10.5MM

HONED

1200 X 200 X 10.5MM, 1200 X 600 X 10.5 MM, 600 X 600 X 10.5 MM, 800 X 800 X 10.5MM

GRIP

1200 X 200 X 10.5MM, 1200 X 600 X 10.5 MM, 600 X 600 X 10.5 MM



BISCOTTI

NATURAL

1200 X 200 X 10.5MM, 1200 X 600 X 10.5 MM, 600 X 300 X 10.5 MM, 600 X 600 X 10.5 MM, 800 X 800 X 10.5MM

HONED

1200 X 200 X 10.5MM, 1200 X 600 X 10.5 MM, 600 X 600 X 10.5 MM, 800 X 800 X 10.5MM

GRIP

1200 X 200 X 10.5MM, 1200 X 600 X 10.5 MM, 600 X 600 X 10.5 MM

SLIP RESISTANCE

Any queries about slip resistance please contact us.

APPLICATION

Point Zero is suitable for:

PTV

96 Rubber

96 Rubber

Wet Dry Wet Dry R Rating

Natural AOR AOR AOR AOR R9

Honed AOR AOR AOR AOR AOR

Grip AOR AOR AOR AOR R11 A B C



Exterior



Heavy Footfall



Interior



Skirting



Stairs

ORDER A FREE SAMPLE

+44(0) 24 7642 2580

design@kinorigo.com

Request 100 X 100 sample

Colour representations on this sheet may not be exact.
Take care when choosing your tiles, make sure you order a sample

Technical Specifications

	Norm	Average value
Water absorbtion	EN ISO 10545_3	<0,5%
Flexular strength (MOR)	EN ISO 10545_4	50 N/mm ²
Breaking strength	EN ISO 10545_4	>1300 N
Slip Resistance	DIN 51130	R9 A Natural R11 A+B+C
Abrasion Resistance	EN ISO 10545_6	<175mm ³
Frost resistance	EN ISO 10545_12	YES
Stain resistance	EN ISO 10545_14	YES

Packaging Information

Finish	Size	Pieces/box	Weight/box	Sqm/box	Boxes/pallet	Weight/pallet	Sqm/pallet
Natural/Honed/Grip	1200 x 600 x 10.5mm	2	34	1,44	20	680	28,80
Natural/Honed/Grip	1200 x 200 x 10.5mm	5	28	1,20	24	672	28,80
Natural/Honed/Grip	600 x 600 x 10.5mm	3	25,5	1,08	32	816	34,56
Natural/Honed/Grip	600 x 300 x 10.5mm	6	25,5	1,08	32	816	34,56
Natural/Honed/Grip	800 x 800 x 10.5mm	2	30	1,28	40	1200	51,20



POINT ZERO MILK



POINT ZERO MILK



POINT ZERO CLOUD



POINT ZERO CLOUD



POINT ZERO CLOUD



POINT ZERO ASH



POINT ZERO RICE



POINT ZERO RICE



POINT ZERO ROPE



POINT ZERO BISCOTTI



POINT ZERO ALL

KINORIGO®
live.design.

+44(0) 24 7642 2580 design@kinorigo.com