NATURAL STONE

KINORIGO®

TECHNICAL SHEET

Agrassi Cream

COLOURS:



AGRASSI CREAM

FINISHES:

POLISHED

SIZES:

CUT TO SIZE BESPOKE TO REQUIREMENTS

SLIP RESISTANCE

Any queries about slip resistance please contact us.

	PTV				
	96 Rubber		55 Rubber		
	Wet	Dry	Wet	Dry	R Rating
Polished	AOR	AOR	AOR	AOR	AOR

APPLICATION

Agrassi Cream is suitable for:

Heavy Footfall

Interior

Skirting

Stairs

ORDER A FREE SAMPLE

+44(0) 24 7642 2580

Request 100 X 100 sample

design@kinorigo.com

Colour representations on this sheet may not be exact.
Take care when choosing your tiles, make sure you order a sample

Technical Specifications

	Norm	Average value

Water absorbtion	TS EN 13755	0,6%
Flexular strength (MOR)	TS EN 12372	18 kg/cm2
Abrasion resistance	EN ISO 10545_6	5.77 cm3

Packaging Information



AGRASSI CREAM AGRASSI-CREAM




AGRASSI CREAM AGRASSI-CREAM



AGRASSI CREAM AGRASSI-CREAM



AGRASSI CREAM AGRASSI-CREAM



AGRASSI CREAM AGRASSI-CREAM



AGRASSI CREAM AGRASSI-CREAM