NATURAL STONE

TECHNICAL SHEET

KINORIGO. Azul Bogniva

SIZES:

1			2 - 2 - 2 - 1 - 1	12
				ALCONOMIC DE LA CONTRACTÓ
				15 tours for
				(CAUDA T S
				6 -
				1-10 10-71-0
and the second second				and the second second
		5		51
				1-2-2
				1. 2. 1. 2. 4
				STATISTICS.
				100000000
	if the second	Etra .		
			1 Carton	19
				Contraction of the
				1000
				Sec. Barriel
				1 million and
		a surger	- mine	and the second s
	and the state of the			
				1000
				Section States
	1 1			
and the second second				

COLOURS:

HONED	CUT TO SIZE BESPOKE TO REQUIREMENTS
POLISHED	CUT TO SIZE BESPOKE TO REQUIREMENTS

AZUL BOQUIRA

SLIP RESISTANCE

Any queries about slip

resistance please contact us.

FINISHES:

APPLICATION

Azul Boquira is suitable for:

PTV								
	96 Rubber 55 Rubber				Heavy Footfall	Interior	Mosaics	
	Wet	Dry	Wet	Dry	R Rating	(\mathbb{D})	F	
Honed	AOR	AOR	AOR	AOR	AOR	Skirting	Stairs	
Polished	AOR	AOR	AOR	AOR	AOR			

ORDER A FREE SAMPLE

+44(0) 24 7642 2580

Request 100 X 100 sample

design@kinorigo.com

Colour representations on this sheet may not be exact. Take care when choosing your tiles, make sure you order a sample

Packaging Information



AZUL BOQUIRA AZUL-BOQUIRA

