


COLOURS:



AZUL VALVERDE

FINISHES:

POLISHED

CUT TO SIZE BESPOKE TO REQUIREMENTS

BRUSHED

CUT TO SIZE BESPOKE TO REQUIREMENTS

HONED

CUT TO SIZE BESPOKE TO REQUIREMENTS

SIZES:

SLIP RESISTANCE

Any queries about slip resistance please contact us.

APPLICATION

Azul Valverde is suitable for:

	PTV				R Rating
	96 Rubber		96 Rubber		
	Wet	Dry	Wet	Dry	
Honed	AOR	AOR	AOR	AOR	AOR
Polished	AOR	AOR	AOR	AOR	AOR
Brushed	AOR	AOR	AOR	AOR	AOR



Exterior



Heavy Footfall



Interior



Mosaics



Skirting



Stairs

ORDER A FREE SAMPLE

+44(0) 24 7642 2580

Request 100 X 100 sample

design@kinorigo.com

Colour representations on this sheet may not be exact.

Take care when choosing your tiles, make sure you order a sample

	Norm	Average value
Apparent Density	EN 1936	2620 kg/m ³
Flexular strength	EN 12372	13,1 Mpa
Open Porosity	EN 1936	2,5%
Abrasion Resistance	EN 14157	22,5 mm

Packaging Information



AZUL VALVERDE ALL



AZUL VALVERDE ALL



AZUL VALVERDE AZUL-VALVERDE



AZUL VALVERDE AZUL-VALVERDE

KINORIGO®
live.design.

+44(0) 24 7642 2580 design@kinorigo.com