


Absolute Calacatta

COLOURS:



CALACATTA

FINISHES:

POLISHED

1000 X 1000 X 6MM, 1500 X 1000 X 6MM, 1500 X 1500 X 6MM,
1500 X 750 X 6MM, 3000 X 1000 X 6MM, 3000 X 1500 X 6MM, 750
X 375 X 6MM, 750 X 750 X 6MM

NATURAL

1000 X 1000 X 6MM, 1500 X 1000 X 6MM, 1500 X 1500 X 6MM,
1500 X 750 X 6MM, 3000 X 1000 X 6MM, 3000 X 1500 X 6MM, 750
X 375 X 6MM, 750 X 750 X 6MM

SIZES:

SLIP RESISTANCE

Any queries about slip resistance please contact us.

	PTV				R Rating
	96 Rubber		55 Rubber		
	Wet	Dry	Wet	Dry	
Polished	AOR	AOR	AOR	AOR	R9
Natural	AOR	AOR	AOR	AOR	R9

APPLICATION

Absolute Calacatta is suitable for:



Exterior



Heavy Footfall



Interior



Skirting



Stairs

ORDER A FREE SAMPLE

+44(0) 24 7642 2580

Request 100 X 100 sample

design@kinorigo.com

Colour representations on this sheet may not be exact.
Take care when choosing your tiles, make sure you order a sample

Technical Specifications

	Norm	Average value
Water absorption	EN ISO 10545_3	5 – 8%
Breaking strength	EN ISO 10545_4	1300 N
Flexular strength (MOR)	EN ISO 10545_4	49 N/mm ²
Abrasion resistance	EN ISO 10545_6	<140 mm ³
Frost resistance	EN ISO 10545_12	YES
Slip resistance	DIN 51130	R9

Packaging Information

Finish	Size	Pieces/Pallet	Weight/pallet	Sqm/pallet
Polished/Natural	3000 x 1500 x	12	870,000	54,00
	6mm			
Polished/Natural	3000 x 1000 x	16	776,00	48,00
	6mm			
Polished/Natural	1500 x 1500 x 6mm	48	1602,00	108,00
Polished/Natural	1500 x 1000 x 6mm	40	912,00	60,00
Polished/Natural	1000 x 1000 x 6mm	52	783,50	52,00
Polished/Natural	1500 x 750 x 6mm	52	876,00	58,50
Polished/Natural	750 x 750 x 6mm	114	954,82	64,13
Polished/Natural	750 x 375 x 6mm	264	1096,5	74,25



ABSOLUTE CALACATTA CALACATTA



ABSOLUTE CALACATTA CALACATTA



ABSOLUTE CALACATTA CALACATTA



ABSOLUTE CALACATTA CALACATTA



ABSOLUTE CALACATTA CALACATTA



ABSOLUTE CALACATTA CALACATTA



ABSOLUTE CALACATTA CALACATTA



ABSOLUTE CALACATTA CALACATTA

KINORIGO®
live.design.

+44(0) 24 7642 2580 design@kinorigo.com