PORCELAIN

KINORIGO®

TECHNICAL SHEET

Absolute Eramosa

COLOURS: **FINISHES:** **SIZES:**



ERAMOSA

POLISHED 1500 X 1500 X 6MM, 1500 X 750 X 6MM, 3000 X 1500 X 6MM

SLIP RESISTANCE

Any queries about slip resistance please contact us.

	PTV				
	96 Rubber		55 Rubber		
	Wet	Dry	Wet	Dry	R Rating
Polished	AOR	AOR	AOR	AOR	R9

APPLICATION

Absolute Eramosa is suitable for:

Exterior

Heavy Footfall

Interior

Skirting

Stairs

ORDER A FREE SAMPLE

+44(0) 24 7642 2580

Request 100 X 100 sample

design@kinorigo.com

Colour representations on this sheet may not be exact.
Take care when choosing your tiles, make sure you order a sample

Technical Specifications

	Norm	Average value
Water absorbtion	EN ISO 10545_3	5 – 8%
Breaking strength	EN ISO 10545_4	1300 N
Flexular strength (MOR)	EN ISO 10545_4	49 N/mm2
Abrasion resistance	EN ISO 10545_6	<140 mm3
Frost resistance	EN ISO 10545_12	YES
Slip resistance	DIN 51130	R9

Packaging Information

Finish	Size	Pieces/Pallet	Weight/pallet	Sqm/pallet
Polished	3000 x 1500 x 6mm	12	870,000	54,00
Polished	1500 x 1500 x 6mm	48	1602,00	108,00
Polished	1500 x 750 x 6mm	52	876,00	58,50



ABSOLUTE ERAMOSA ERAMOSA



ABSOLUTE ERAMOSA ERAMOSA