

Absolute Estremoz Crema

COLOURS:

FINISHES:

SIZES:



ESTRAMOZ CREMA

POLISHED

1500 X 1500 X 6MM, 1500 X 750 X 6MM, 3000 X 1500 X 6MM, 750 X 375 X 6MM, 750 X 750 X 6MM

SLIP RESISTANCE

Any queries about slip resistance please contact us.

		PTV			
		96 Rubber	55 Rubber		
		Wet	Dry	Wet	Dry
		R Rating			
Polished		AOR	AOR	AOR	AOR
		R9			

APPLICATION

Absolute Estremoz Crema is suitable for:



Exterior



Heavy Footfall



Interior



Skirting



Stairs

ORDER A FREE SAMPLE

+44(0) 24 7642 2580

Request 100 X 100 sample

design@kinorigo.com

Colour representations on this sheet may not be exact.
Take care when choosing your tiles, make sure you order a sample

Technical Specifications

Norm Average value

Water absorption	EN ISO 10545_3	5 – 8%
Breaking strength	EN ISO 10545_4	1300 N
Flexural strength (MOR)	EN ISO 10545_4	49 N/mm ²
Abrasion resistance	EN ISO 10545_6	<140 mm ³
Frost resistance	EN ISO 10545_12	YES
Slip resistance	DIN 51130	R9

Packaging Information

Finish	Size	Pieces/Pallet	Weight/pallet	Sqm/pallet
Polished	3000 x 1500 x 6mm	12	870,000	54,00
Polished	1500 x 1500 x 6mm	48	1602,00	108,00
Polished	1500 x 750 x 6mm	52	876,00	58,50
Polished	750 x 750 x 6mm	114	954,82	64,13
Polished	750 x 375 x 6mm	264	1096,5	74,25



ABSOLUTE ESTREMOZ CREMA ESTRAMOZ-CREMA