

PORCELAIN

KINORIGO®

TECHNICAL SHEET

Arona

COLOURS:

FINISHES:

SIZES:



CLAY

NATURAL


1200 X 1200 X 6MM, 2600 X 1200 X 6MM



CREAM

NATURAL


1200 X 1200 X 6MM, 2600 X 1200 X 6MM



DOVE

NATURAL


1200 X 1200 X 6MM, 2600 X 1200 X 6MM



GREY

NATURAL

1200 X 1200 X 6MM, 2600 X 1200 X 6MM



SLATE

NATURAL

1200 X 1200 X 6MM, 2600 X 1200 X 6MM

SLIP RESISTANCE

Any queries about slip resistance please contact us.

PTV					
96 Rubber		55 Rubber			
Wet	Dry	Wet	Dry	R Rating	
Natural	AOR	AOR	AOR	AOR	R10

APPLICATION

Arona is suitable for:



Exterior



Heavy Footfall



Interior



Mosaics



Pool Edgings



Skirting



Stairs



Wet Areas

ORDER A FREE SAMPLE

+44(0) 24 7642 2580

Request 100 X 100 sample

design@kinorigo.com

Colour representations on this sheet may not be exact.
Take care when choosing your tiles, make sure you order a sample

Technical Specifications

	Norm	Average value
Water absorption	EN ISO 10545_3	<0.1%
Abrasion resistance	EN ISO 10545_6	<175mm ³
Flexural strength (MOR)	EN ISO 10545_4	50 N/mm ²
Slip resistance	DIN 51130	R10
Frost resistance	EN ISO 10545_12	YES
Stain resistance	EN ISO 10545_14	YES

Packaging Information

Finish	Size	Pieces/box	Weight/box	Sqm/box	Boxes/pallet	Weight/pallet	Sqm/pallet
Natural	2600 x 1200 x 6mm	1	44	3,12	20	880	62,40
Natural	1200 x 1200 x 6mm	2	40,6	2,88	25	1015	72



ARONA CLAY



ARONA CLAY



ARONA CREAM



ARONA CREAM



ARONA CREAM



ARONA DOVE



ARONA DOVE



ARONA GREY



ARONA SLATE



ARONA SLATE

KINORIGO®
live.design.

+44(0) 24 7642 2580 design@kinorigo.com