

PORCELAIN

KINORIGO®

Raima

TECHNICAL SHEET

COLOURS:	FINISHES:	SIZES:
 **IRON**	**NATURAL**	2600 X 1200 X 6MM, 1200 X 600 X 6MM, 1200 X 1200 X 6MM
 **SAND**	**NATURAL**	1200 X 600 X 6MM, 1200 X 1200 X 6MM, 2600 X 1200 X 6MM
 **STONE**	**NATURAL**	1200 X 1200 X 6MM, 1200 X 600 X 6MM, 2600 X 1200 X 6MM
 **CLAY**	**NATURAL**	2600 X 1200 X 6MM, 1200 X 1200 X 6MM, 1200 X 600 X 6MM
 **METAL**	**NATURAL**	2600 X 1200 X 6MM, 1200 X 1200 X 6MM, 1200 X 600 X 6MM

SLIP RESISTANCE

Any queries about slip resistance please contact us.

	PTV				
	96 Rubber		55 Rubber		
	Wet	Dry	Wet	Dry	R Rating
Natural	AOR	AOR	AOR	AOR	R10

APPLICATION

Raima is suitable for:


Exterior


Interior


Mosaics


Skirting


Stairs


Wet Areas

ORDER A FREE SAMPLE

+44(0) 24 7642 2580 Request 100 X 100 sample design@kinorigo.com

Colour representations on this sheet may not be exact.
Take care when choosing your tiles, make sure you order a sample

Technical Specifications

	Norm	Average value
Water absorbtion	EN ISO 10545_3	0.1%
Flexular strength (MOR)	EN ISO 10545_4	50 N/mm²
Slip resistance	DIN 51130	R10
Frost resistance	EN ISO 10545_12	YES
Stain resistance	EN ISO 10545_14	YES

Packaging Information

Finish	Size	Pieces/box	Weight/box	Sqm/box	Boxes/pallet	Weight/pallet	Sqm/pallet
Natural	2600 x 1200 x 6mm	1	44,0	3,12	20	880,0	62,40
Natural	1200 x 1200 x 6mm	2	40,6	2,88	25	1015,0	72,00
Natural	1200 x 600 x 6mm	3	30,3	2,16	16	484,8	34,56



RAIMA CLAY



RAIMA CLAY



RAIMA CLAY



RAIMA CLAY



RAIMA CLAY



RAIMA CLAY



RAIMA IRON



RAIMA METAL



RAIMA METAL



RAIMA METAL



RAIMA METAL



RAIMA METAL



RAIMA METAL



RAIMA SAND



RAIMA SAND



RAIMA SAND



RAIMA SAND



RAIMA STONE



RAIMA STONE



RAIMA STONE

+44(0) 24 7642 2580 design@kinorigo.com