

Rocky

COLOURS:

FINISHES:


SIZES:



DARK GREY

NATURAL

1000 X 1000 X 6MM, 3000 X 1000 X 6MM



GREIGE

NATURAL

1000 X 1000 X 6MM, 3000 X 1000 X 6MM



GREY

NATURAL

1000 X 1000 X 6MM, 3000 X 1000 X 6MM



SILVER

NATURAL

1000 X 1000 X 6MM, 3000 X 1000 X 6MM

SLIP RESISTANCE

Any queries about slip resistance please contact us.

APPLICATION

Rocky is suitable for:

PTV								
96 Rubber		55 Rubber			Exterior	Heavy Footfall	Interior	
Wet	Dry	Wet	Dry	R Rating				
Natural	AOR	AOR	AOR	AOR	R9	Mosaics	Skirting	Stairs

ORDER A FREE SAMPLE

+44(0) 24 7642 2580

Request 100 X 100 sample

design@kinorigo.com

Colour representations on this sheet may not be exact.
Take care when choosing your tiles, make sure you order a sample

Technical Specifications

	Norm	Average value
Water absorbtion	EN ISO 10545_3	<0,5%
Flexular strength (MOR)	EN ISO 10545_4	49 N/mm ²
Breaking strength	EN ISO 10545_4	>700 N
Slip Resistance	DIN 51130	R9
	EN ISO 10545_6	140mm ³
Frost resistance	EN ISO 10545_12	YES
Stain resistance	EN ISO 10545_14	YES

Packaging Information

Finish	Size	Pieces/box	Weight/pallet	Sqm/pallet
Natural	1000 x 1000 x 6mm	24	382,50	24,00
Natural	3000 x 1000 x 6mm	16	870,00	54,00



ROCKY DARK-GREY



ROCKY GREIGE



ROCKY GREY



ROCKY SILVER