PORCELAIN

KINORIGO®

TECHNICAL SHEET

# Absolute Statuario Light

**COLOURS:**



**STATUARIO LIGHT**

**FINISHES:**

**POLISHED**

**SIZES:**

1500 X 1500 X 6MM, 1500 X 750 X 6MM, 3000 X 1500 X 6MM, 750 X 375 X 6MM, 750 X 750 X 6MM

## SLIP RESISTANCE

Any queries about slip resistance please contact us.

| | PTV | | | | |
|---|---|---|---|---|---|
| | 96 Rubber | | 55 Rubber | | |
| | Wet | Dry | Wet | Dry | R Rating |
| Polished | AOR | AOR | AOR | AOR | R9 |

## APPLICATION

Absolute Statuario Light is suitable for:

Heavy Footfall

Interior

Skirting

Stairs

## ORDER A FREE SAMPLE

+44(0) 24 7642 2580

Request 100 X 100 sample

design@kinorigo.com

Colour representations on this sheet may not be exact.
Take care when choosing your tiles, make sure you order a sample

## Technical Specifications

| | Norm | Average value |
|---|---|---|

| | | |
|---|---|---|
| Water absorbtion | EN ISO 10545_3 | 5 – 8% |
| Breaking strength | EN ISO 10545_4 | 1300 N |
| Flexular strength (MOR) | EN ISO 10545_4 | 49 N/mm2 |
| Abrasion resistance | EN ISO 10545_6 | <140 mm3 |
| Frost resistance | EN ISO 10545_12 | YES |
| Slip resistance | DIN 51130 | R9 |

## Packaging Information

| Finish | Size | Pieces/Pallet | Weight/pallet | Sqm/pallet |
|---|---|---|---|---|
| Polished | 3000 x 1500 x 6mm | 12 | 870,000 | 54,00 |
| Polished | 1500 x 1500 x 6mm | 48 | 1602,00 | 108,00 |
| Polished | 1500 x 750 x 6mm | 52 | 876,00 | 58,50 |
| Polished | 750 x 750 x 6mm | 114 | 954,82 | 64,13 |
| Polished | 750 x 375 x 6mm | 264 | 1096,5 | 74,25 |