



*Dalako***COLOURS:****CARDOSO****CHIARO****GRIGIO****QUARTZ****FINISHES:****NATURAL**

1500 X 750 X 10MM, 750 X 750 X 10MM

POLISHED

1500 X 750 X 10MM, 750 X 750 X 10MM

NATURAL

1500 X 750 X 10MM, 750 X 750 X 10MM

POLISHED

1500 X 750 X 10MM, 750 X 750 X 10MM

NATURAL

1500 X 750 X 10MM, 750 X 750 X 10MM

POLISHED

1500 X 750 X 10MM, 750 X 750 X 10MM

NATURAL

1500 X 750 X 10MM, 750 X 750 X 10MM

POLISHED

1500 X 750 X 10MM, 750 X 750 X 10MM

SIZES:**SLIP RESISTANCE**

Any queries about slip resistance please contact us.

APPLICATION

Dalako is suitable for:

PTV							
96 Rubber		55 Rubber			Exterior	Heavy Footfall	Interior
	Wet	Dry	Wet	Dry	R Rating		
Natural	AOR	AOR	AOR	AOR	R10 A	Skirting	Stairs
Polished	AOR	AOR	AOR	AOR	AOR		

ORDER A FREE SAMPLE

+44(0) 24 7642 2580

Request 100 X 100 sample

design@kinorigo.com

Colour representations on this sheet may not be exact.
Take care when choosing your tiles, make sure you order a sample

Technical Specifications

	Norm	Average value
Water absorbtion	EN ISO 10545_3	<0,1%
Breaking strength	EN ISO 10545_4	3000 N
Flexular strength (MOR)	EN ISO 10545_4	>45 N/mm2
Abrasion resistance	EN ISO 10545_6	140 mm3
Frost resistance	EN ISO 10545_12	YES
Slip resistance	DIN 51130	R10 A
Stain resistance	EN ISO 10545_14	YES

Packaging Information



DALAKO CARDOSO



DALAKO CARDOSO



DALAKO CARDOSO



DALAKO CHIARO



DALAKO CHIARO



DALAKO CHIARO



DALAKO GRIGIO



DALAKO GRIGIO



DALAKO GRIGIO

KINORIGO®
live.design.

+44(0) 24 7642 2580 design@kinorigo.com