

*Torino*

**COLOURS:**

**FINISHES:**

**SIZES:**



**ANTIQUÉ WHITE**

**NATURAL**

1200 X 1200 X 10.5MM, 1200 X 600 X 10.5 MM, 600 X 600 X 10.5 MM, 600 X 300 X 10.5 MM

**POLISHED**

1200 X 1200 X 10.5MM, 1200 X 600 X 10.5 MM

**BUSHHAM**

600 X 600 X 10.5 MM, 600 X 300 X 10.5 MM

**MERED**



**STONY GREY**

**NATURAL**

1200 X 1200 X 10.5MM, 1200 X 600 X 10.5 MM, 600 X 600 X 10.5 MM, 600 X 300 X 10.5 MM

**POLISHED**

1200 X 1200 X 10.5MM, 1200 X 600 X 10.5 MM

**BUSHHAM**

600 X 600 X 10.5 MM, 600 X 300 X 10.5 MM

**MERED**



**SLATE**


**NATURAL**

1200 X 1200 X 10.5MM, 1200 X 600 X 10.5 MM, 600 X 600 X 10.5 MM, 600 X 300 X 10.5 MM

**BUSHHAM**

600 X 600 X 10.5 MM, 600 X 300 X 10.5 MM

**MERED**



**BLACK SLATE**

**NATURAL**

1200 X 1200 X 10.5MM, 1200 X 600 X 10.5 MM, 600 X 600 X 10.5 MM, 600 X 300 X 10.5 MM

**BUSHHAM**

600 X 600 X 10.5 MM, 600 X 600 X 10.5 MM

**MERED**

## SLIP RESISTANCE

Any queries about slip resistance please contact us.

PTV

96 Rubber 55 Rubber

Wet Dry Wet Dry R Rating

Bushhammered AOR AOR AOR AOR AOR

Natural AOR AOR AOR AOR AOR

Polished AOR AOR AOR AOR AOR

## APPLICATION

Torino is suitable for:



Exterior



Heavy Footfall



Interior



Skirting



Stairs

## ORDER A FREE SAMPLE

+44(0) 24 7642 2580

Request 100 X 100 sample

design@kinorigo.com

Colour representations on this sheet may not be exact.  
Take care when choosing your tiles, make sure you order a sample

## Technical Specifications

	Norm	Average value
Water absorption	EN ISO 10545_3	<0,1%
Flexural strength (MOR)	EN ISO 10545_4	>45 N/mm <sup>2</sup>
Breaking strength	EN ISO 10545_4	3000 N
Abrasion Resistance	EN ISO 10545_6	<140mm <sup>3</sup>
Frost resistance	EN ISO 10545_12	YES
Stain resistance	EN ISO 10545_14	YES

## Packaging Information



TORINO ANTIQUE-WHITE



TORINO STONY-GREY



TORINO SLATE



TORINO BLACK-SLATE

**KINORIGO®**  
live.design.

+44(0) 24 7642 2580    [design@kinorigo.com](mailto:design@kinorigo.com)