

COLOURS:

FINISHES:

SIZES:



CHARRED WOOD

NATURAL

1200 X 150 X 10.5MM, 1200 X 200 X 10.5MM, 1800 X 200 X 10.5MM,
1800 X 265 X 10.5MM

SLIP RESISTANCE

Any queries about slip resistance please contact us.

PTV

96 Rubber

55 Rubber

Wet

Dry

Wet

Dry

R Rating

Natural

AOR

AOR

AOR

AOR

R9

APPLICATION

Charred Wood is suitable for:



Exterior



Heavy Footfall



Interior



Skirting



Stairs

ORDER A FREE SAMPLE

+44(0) 24 7642 2580

Request 100 X 100 sample

design@kinorigo.com

Colour representations on this sheet may not be exact.
Take care when choosing your tiles, make sure you order a sample

Technical Specifications

Norm

Average value

Water absorbtion	EN ISO 10545_3	<0,5%
Flexular strength (MOR)	EN ISO 10545_4	>35 N/mm2
Frost resistance	EN ISO 10545_12	YES
Slip resistance	DIN 51130	R9
Stain resistance	EN ISO 10545_14	YES

Packaging Information

Finish	Size	Pieces/box	Weight/box	Sqm/box	Boxes/pallet	Weight/pallet	Sqm/pallet
Natural	1800 x 265 x 10.5mm	3	34,00	1,44	36	1224,00	51,84
Natural	1800 x 200 x 10.5mm	4	34,00	1,44	40	1360,00	57,60
Natural	1200 x 200 x 10.5mm	5	28,00	1,20	24	672,00	28,80
Natural	1200 x 150 x 10.5mm	6	25,50	1,08	27	688,50	29,16



CHARRED WOOD CHARRED-WOOD



CHARRED WOOD CHARRED-WOOD



CHARRED WOOD CHARRED-WOOD

